

ElectroChill Chiller



ElectroChill is the solution for cooled water to cater the need of chilled water in aquatic animals.

- Environmentally friendly R410A refrigerant.
- High energy efficiency ratio (EER) for greater power conversion.
- Low footprint to ease installation.



Power Input	2.3 kW
Current	12 A
Cooling Capacity	9 kW
Refrigerant	R410A
Min / Max Water Temperature	6/40°C
EER	3.6
Min / Max Water Flow Rate	114 / 227 lpm
Supply Voltage	240 VAC/ 50 Hz
Unit Dry Weight	55 kg
Dimension W x L x H	361 mm x 1269 mm x 717 mm
Water Connections Size	40 mm

OFFICES - AUSTRALIA

NSW - Sydney (Head Office)
Tel: +61 2 9898 8600
QLD - Brisbane
Tel: +61 7 3299 9900
VIC/TAS - Melbourne
Tel: +61 3 9764 1211
WA - Perth
Tel: +61 8 9273 1900
SA/NT - Adelaide
Tel: +61 8 8244 6000
ACT Distribution
Tel: +61 2 6280 6476

OFFICES - OVERSEAS

Waterco (Europe) Limited
Sittingbourne, Kent, UK
Tel: +44 (0) 1795 521 733
Waterco (USA) Inc
Augusta, Georgia, USA
Tel: +1 706 793 7291
Waterco Canada
Boucherville, Quebec, Canada
Tel: +1 450 748 1421
Waterco (NZ) Limited
Auckland, New Zealand
Tel: +64 9 525 7570
Waterco (C) Limited
Guangzhou, China
Tel: +86 20 3222 2180
Waterco (Far East) Sdn Bhd
Selangor, Malaysia
Tel: +60 3 6145 6000
PT Waterco Indonesia
Jakarta, Indonesia
Tel: +62 21 4585 1481
Waterco Singapore Intl Pte Ltd
Nehsons Building, Singapore
Tel: +65 6344 2378

DISTRIBUTED BY:



ZZB2017_03/21